

TRAVERTINO 2.0



QUALITY. GUARANTEED.



FLOOR White 80x80cm

PORCELAIN

Bring home the beauty of nature with TRAVERTINO 2.0 by MML®. This travertine design adds polished elegance to your indoor spaces in 2 colour options - White and Ivory.

TRAVERTINO 2.0



QUALITY. GUARANTEED.



WHITE

POLISHED PC143



80x80cm



60x60cm



Floor



Indoor



Wall


V3

Random




IVORY

POLISHED PC148



80x80cm



60x60cm



Floor



Indoor



Wall

V3

Random

PACKING LIST

SIZE	FINISH	THICKNESS (mm)	PCS / M2	PCS / CTN	CTN / PLT	PLT / 20'FCL	AVG WEIGHT / CTN (KG)	AVG WEIGHT / PLT (KG)
60x60cm	Polished	10.0	2.78	4	36	21	35.00	1,260
80x80cm	Polished	11.0	1.56	3	28	18	53.00	1,484

TECHNICAL SPECIFICATION

MML PORCELAIN E ≤ 0.5% (B1a, ANNEX G)

TECHNICAL FEATURES	STANDARDS	INTERNATIONAL STANDARDS	MML TYPICAL STANDARDS
DIMENSIONAL CHARACTERISTICS			
Length & Width	ISO 10545-2 / EN 98	±0.60% max±2.0mm	±0.25% max±2.0mm
Thickness	ISO 10545-2 / EN 98	±5.00% max±0.5mm	±5.00% max±0.5mm
Straightness of Sides	ISO 10545-2 / EN 98	±0.50% max±1.5mm	±0.25% max±1.5mm
Rectangularity	ISO 10545-2 / EN 98	±0.50% max±2.0mm	±0.30% max±2.0mm
Surface Flatness	ISO 10545-2 / EN 98	±0.50% max±2.0mm	±0.25% max±2.0mm
CHEMICAL PROPERTIES			
Resistance to Household Chemicals & Swimming Pool Salts	ISO 10545-13 / EN 106	Min GB	GB
Resistance to Staining	ISO 10545-14	Min Class 3	Class 3
PHYSICAL PROPERTIES			
Water Absorption	ISO 10545-3 / EN 99	Group B1a, E≤0.5%	≤0.5%
Breaking Strength	ISO 10545-4 / EN 100	Min 1300 N	1300 N
Modulus of Rupture	ISO 10545-4 / EN 100	Min 35 N / mm ²	> 35 N / mm ² (Depending on Series)
Resistance to Surface Abrasion	ISO 10545-7 / EN 154	Report Abrasion Class	Glazed: Class 2 – 4 (Depending on Glaze Type)
Resistance to Deep Abrasion	ISO 10545-6 / EN 102	Max 175mm ³	Unglazed: Max 150mm ³