

KURIN




QUALITY. GUARANTEED.



FLOOR White 60x60cm

PORCELAIN

The super white KURIN by MML® captivates with its refined polished finish. A class above elegant, KURIN tastefully brings openness to your indoor spaces.



WHITE
POLISHED P628



60x60cm



Floor



Indoor



Wall

V1

PACKING LIST

SIZE	FINISH	THICKNESS (mm)	PCS / M2	PCS / CTN	CTN / PLT	PLT / 20'FCL	AVG WEIGHT / CTN (KG)	AVG WEIGHT / PLT (KG)
60x60cm	Polished	9.5	2.78	4	40	20	32.00	1,300

TECHNICAL SPECIFICATION

MML PORCELAIN E ≤ 0.5% (B1a, ANNEX G)

TECHNICAL FEATURES	STANDARDS	INTERNATIONAL STANDARDS	MML TYPICAL STANDARDS
DIMENSIONAL CHARACTERISTICS			
Length & Width	ISO 10545-2 / EN 98	±0.60% max±2.0mm	±0.25% max±2.0mm
Thickness	ISO 10545-2 / EN 98	±5.00% max±0.5mm	±5.00% max±0.5mm
Straightness of Sides	ISO 10545-2 / EN 98	±0.50% max±1.5mm	±0.25% max±1.5mm
Rectangularity	ISO 10545-2 / EN 98	±0.50% max±2.0mm	±0.30% max±2.0mm
Surface Flatness	ISO 10545-2 / EN 98	±0.50% max±2.0mm	±0.25% max±2.0mm
CHEMICAL PROPERTIES			
Resistance to Household Chemicals & Swimming Pool Salts	ISO 10545-13 / EN 106	Min GB	GB
Resistance to Staining	ISO 10545-14	Min Class 3	Class 3
PHYSICAL PROPERTIES			
Water Absorption	ISO 10545-3 / EN 99	Group B1a, E≤0.5%	≤0.5%
Breaking Strength	ISO 10545-4 / EN 100	Min 1300 N	1300 N
Modulus of Rupture	ISO 10545-4 / EN 100	Min 35 N / mm ²	> 35 N / mm ² (Depending on Series)
Resistance to Surface Abrasion	ISO 10545-7 / EN 154	Report Abrasion Class	Glazed: Class 2 – 4 (Depending on Glaze Type)
Resistance to Deep Abrasion	ISO 10545-6 / EN 102	Max 175mm ³	Unglazed: Max 150mm ³