

STONEWAVE



QUALITY. GUARANTEED.

The iconic slatestone look has stood the test of time as the all-time favourite flooring choice. Stonewave features the characteristic veining and undulations of natural slatestone with rugged good looks and versatility. Bring home warmth and comfort with the off-white hue of Stonewave in Bianco. Add natural charm to your spaces with the neutral mid-toned grey of Stonewave in Grigio. Or opt for Stonewave in Antracite to achieve a classy in-depth look.

STONEWAVE



STONEWAVE

COLOURS

A new wave of natural stone aesthetics.



WALL&FLOOR: ANTRACITE **SMSTO3** 30x60cm / 12"x24"
WALL: BIANCO **SMSTO1** 30x60cm / 12"x24"



SMSTO1
BIANCO



SMSTO2
GRIGIO



SMSTO3
ANTRACITE



WALL&FLOOR: BIANCO **SMSTO1** 30x60cm / 12"x24"



FLOOR: GRIGIO **SMST02** 30x60cm / 12"x24"

STONEWAVE

Product Information




SMSTO1 / BIANCO



SMSTO3 / ANTRACITE



SMSTO2 / GRIGIO



MATT 60x60cm 24"x24" 6 Faces	MATT 30x60cm 12"x24" 12 Faces
--	---

- Floor
- Wall
- Outdoor
- Indoor

* Colours and tile designs shown above are for illustration purposes. Please refer to actual tiles for final selection.

TECHNICAL SPECIFICATION MML PORCELAIN (RECTIFIED)


E ≤ 0.5% (Bla, ANNEX G)

TECHNICAL FEATURES	STANDARDS	INTERNATIONAL STANDARDS	MML TYPICAL STANDARDS
DIMENSIONAL CHARACTERISTICS			
Length & Width	ISO 10545-2	± 0.30% max ± 1.0mm	± 0.25% max ± 1.0mm
Thickness	ISO 10545-2	± 5.00% max ± 0.5mm	± 5.00% max ± 0.5mm
Straightness of Sides	ISO 10545-2	± 0.30% max ± 0.8mm	± 0.25% max ± 0.8mm
Rectangularity	ISO 10545-2	± 0.30% max ± 1.5mm	± 0.30% max ± 1.5mm
Surface Flatness	ISO 10545-2	± 0.40% max ± 1.8mm	± 0.25% max ± 1.8mm
CHEMICAL PROPERTIES			
Resistance to Household Chemicals & Swimming Pool Salts	ISO 10545-13	Min GB	GB
Resistance to Staining	ISO 10545-14	Min Class 3	Class 3
PHYSICAL PROPERTIES			
Water Absorption	ISO 10545-3	Group Bla, E ≤ 0.5%	≤ 0.5%
Breaking Strength	ISO 10545-4	Min 1300 N	1300 N
Modulus of Rupture	ISO 10545-4	Min 35 N / mm ²	> 35 N / mm ² (Depending on Series)
Resistance to Surface Abrasion	ISO 10545-7	Report Abrasion Class	Glazed: Class 2-4 (Depending on Glaze Type)



QUALITY. GUARANTEED.

FOLLOW US ON:



mymml.com



mmlglobal



mmlglobal



The above information serves as a general guideline only. Different types of tiles are made to meet different performance requirements. For legal compliance or for specific product technical performance, please request for a confirmation or test report.