

BRAVESTONE



QUALITY. GUARANTEED.

Bravestone perfectly interprets the rugged characteristics of natural stone. With strong visible veins and a textured surface, Bravestone is designed to create dynamic visual impact in your common areas, yard, balcony and semi-outdoor spaces in a neutral colour palette of Silver, Grigio and Nero.

BRAVESTONE



BRAVESTONE

COLOURS



FLOOR: GRIGIO **SCBRA2** 60x60cm / 24"x24"



SCBRA1
SILVER



SCBRA2
GRIGIO



SCBRA4
NERO

BRAVESTONE

CRYSTAL MATT
60x60cm
24"x24"
6 Faces

CRYSTAL MATT
30x60cm
12"x24"
12 Faces

V2
Rectified
Eco Label
Flat

SCBRA1 / SILVER



60x60cm
24"x24"



30x60cm
12"x24"



FLOOR: SILVER **SCBRA1** 60x60cm / 24"x24"

-  Floor
-  Wall
-  Outdoor
-  Indoor

* Colours and tile designs shown above are for illustration purposes. Please refer to actual tiles for final selection.

BRAVESTONE



CRYSTAL MATT
60x60cm
24"x24"
6 Faces

CRYSTAL MATT
30x60cm
12"x24"
12 Faces

SCBRA2 / GRIGIO



60x60cm
24"x24"



30x60cm
12"x24"

SCBRA4 / NERO



60x60cm
24"x24"



30x60cm
12"x24"



* Colours and tile designs shown above are for illustration purposes. Please refer to actual tiles for final selection.

TECHNICAL SPECIFICATION MML PORCELAIN (RECTIFIED)


E ≤ 0.5% (Bla, ANNEX G)

TECHNICAL FEATURES	STANDARDS	INTERNATIONAL STANDARDS	MML TYPICAL STANDARDS
DIMENSIONAL CHARACTERISTICS			
Length & Width	ISO 10545-2	± 0.30% max ± 1.0mm	± 0.25% max ± 1.0mm
Thickness	ISO 10545-2	± 5.00% max ± 0.5mm	± 5.00% max ± 0.5mm
Straightness of Sides	ISO 10545-2	± 0.30% max ± 0.8mm	± 0.25% max ± 0.8mm
Rectangularity	ISO 10545-2	± 0.30% max ± 1.5mm	± 0.30% max ± 1.5mm
Surface Flatness	ISO 10545-2	± 0.40% max ± 1.8mm	± 0.25% max ± 1.8mm
CHEMICAL PROPERTIES			
Resistance to Household Chemicals & Swimming Pool Salts	ISO 10545-13	Min GB	GB
Resistance to Staining	ISO 10545-14	Min Class 3	Class 3
PHYSICAL PROPERTIES			
Water Absorption	ISO 10545-3	Group Bla, E ≤ 0.5%	≤ 0.5%
Breaking Strength	ISO 10545-4	Min 1300 N	1300 N
Modulus of Rupture	ISO 10545-4	Min 35 N / mm ²	> 35 N / mm ² (Depending on Series)
Resistance to Surface Abrasion	ISO 10545-7	Report Abrasion Class	Glazed: Class 2-4 (Depending on Glaze Type)



QUALITY. GUARANTEED.

FOLLOW US ON:



mymml.com



mmlglobal



mmlglobal



The above information serves as a general guideline only. Different types of tiles are made to meet different performance requirements. For legal compliance or for specific product technical performance, please request for a confirmation or test report.