



MANCHESTER



QUALITY. GUARANTEED.

DESIGNED FOR YOUR OUTDOORS

Sophistication meets functionality with the minimal stone look of Manchester. Suitable for application in common areas, yards, balconies, car porches, semi-outdoor and external spaces, Manchester embodies the strength and performance of natural stone in a structured anti-slip finish.

MANCHESTER




MANCHESTER

COLOURS



WALL&FLOOR: GREY **RGMAN3** 60x60cm / 24"x24"



RGMAN1
AVORIO

RGMAN2
LIGHT GREY

RGMAN3
GREY

RGMAN4
DARK GREY




FLOOR: DARK GREY **RGMAN4** 60x60cm / 24"x24"



FLOOR: LIGHT GREY **RGMAN2** 60x60cm / 24"x24"

MANCHESTER


Product Information




ROUGH
 60x60cm
 24"x24"
 2 Faces

ROUGH
 30x60cm
 12"x24"
 4 Faces

RGMAN1 / AVORIO



RGMAN2 / LIGHT GREY



* Colors and tile designs shown above are for illustration purposes. Please refer to actual tiles for final selection.

MANCHESTER

Product Information




Rectified
Structured
Eco MML


ROUGH
60x60cm
24"x24"
2 Faces

ROUGH
30x60cm
12"x24"
4 Faces

RGMAN3 / GREY



RGMAN4 / DARK GREY



* Colors and tile designs shown above are for illustration purposes. Please refer to actual tiles for final selection.

TECHNICAL SPECIFICATION MML PORCELAIN (RECTIFIED)


E ≤ 0.5% (Bla, ANNEX G)

TECHNICAL FEATURES	STANDARDS	INTERNATIONAL STANDARDS	MML TYPICAL STANDARDS
DIMENSIONAL CHARACTERISTICS			
Length & Width	ISO 10545-2	± 0.30% max ± 1.0mm	± 0.25% max ± 1.0mm
Thickness	ISO 10545-2	± 5.00% max ± 0.5mm	± 5.00% max ± 0.5mm
Straightness of Sides	ISO 10545-2	± 0.30% max ± 0.8mm	± 0.25% max ± 0.8mm
Rectangularity	ISO 10545-2	± 0.30% max ± 1.5mm	± 0.30% max ± 1.5mm
Surface Flatness	ISO 10545-2	± 0.40% max ± 1.8mm	± 0.25% max ± 1.8mm
CHEMICAL PROPERTIES			
Resistance to Household Chemicals & Swimming Pool Salts	ISO 10545-13	Min GB	GB
Resistance to Staining	ISO 10545-14	Min Class 3	Class 3
PHYSICAL PROPERTIES			
Water Absorption	ISO 10545-3	Group Bla, E ≤ 0.5%	≤ 0.5%
Breaking Strength	ISO 10545-4	Min 1300 N	1300 N
Modulus of Rupture	ISO 10545-4	Min 35 N / mm ²	> 35 N / mm ² (Depending on Series)
Resistance to Surface Abrasion	ISO 10545-7	Report Abrasion Class	Glazed: Class 2-4 (Depending on Glaze Type)



QUALITY. GUARANTEED.

FOLLOW US ON:



mymml.com



mmlglobal



mmlglobal



The above information serves as a general guideline only. Different types of tiles are made to meet different performance requirements. For legal compliance or for specific product technical performance, please request for a confirmation or test report.